

CLEAR FOCUS® Tack'em™ Tape 2


Optically Clear Double-sided Adhesive Tape for Use with PosterVue® and Other Window Graphics

Applications: PosterVue window graphics and other graphics for P.O.P, retail window signage, and other advertising and promotions requiring a clear double-sided adhesive tape.

Construction:

Carrier 1-mil optically clear polyester
Adhesives Optically clear permanent and removable acrylic
Liners Permanent side: 1-mil clear polyester film
 Removable side: 1.4-mil blue polyester

Product configuration



Important: Attach the side with the permanent adhesive to the graphic.

- For interior mounting, attach the side with the permanent adhesive to the face of the graphic.
- For exterior mounting, attach the side with the permanent adhesive to the back of the graphic.
- The side with the removable adhesive is designed to be attached to the glass or other mounting surface.
- For small posters, attach strips of Tack'em Tape 2 to the edges of the graphic.
- For posters larger than about 24 inches wide, in addition to the edges we also recommend applying a strip of Tack'em Tape 2 approx. every 12 to 15 inches (length and width) to prevent the poster from sagging.

Typical Performance Values:

Outdoor durability	Up to 2 years		
Typical adhesion values	180° Peel Test		
	<u>Substrate</u>		<u>24 hrs.</u>
	Stainless Steel	Permanent	2.0 lb/in.
	Stainless Steel	Removable	1.0 lb/in.
Static shear (½ in. x ½ in. x 500 grams)	> 24 hours		
Minimum application temperature	50° F (minimum for substrate)		
Service temperature range	20° F to 302° F		
Shelf life	1 year from ship date when stored under proper conditions (70° F and 50% relative humidity)		

Other CLEAR FOCUS mounting products available

- Tack'em™ Tape 1 single-sided clear adhesive tape (for edge sealing)
- AdHereVue® transfer adhesive (for full coverage of graphic)

The above information on physical and chemical characteristics are based on tests believed to be reliable. The values are intended only as a source of information. They are given without guarantee and do not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific application.

CLEAR FOCUS Imaging, Inc.
Tel: 800-307-7990 • 707-544-7990 • Fax: 707-544-1886
Email: headoffice@clearfocus.com • Web: www.clearfocus.com