



CrystalVue™ Silver Glass EtchVue™ EtchVue™

Film:

2- to 3-mil cast PVC on a 3-in. core

Standard roll size:

24 & 48 in. x 25 & 100 ft.

Application:

Architectural, decorative, privacy,
special effects, signage

CrystalVue™ Silver

Product code: CFCYVS

Glass EtchVue™


Product code: CFGETV

EtchVue™

Product code: CFETV



CLEAR FOCUS Imaging, Inc.



CLEAR FOCUS CrystalVue™ Silver FILM

Product Code: CFCYVS

CLEAR FOCUS Glass EtchVue™ FILM

Product Code: CFGETV

CLEAR FOCUS EtchVue™ FILM

Product Code: CFETV

Interior/Exterior Adhesive Mount Product Data

2- to 3-mil cast vinyl film that combines flakes and pigments to create a frosted or etched effect on glass or other optically clear substrates; or on smooth surfaces, such as mirrors. The films feature a low gloss and a high degree of transparency, are printable, and can be cut by steel rule, thermal die-cutter or plotter.

Applications	Architectural, decorative, privacy, special effects, text/signage (printed or unprinted).
Composition	Cast vinyl
Adhesive	Permanent solvent acrylic
Vinyl Thickness (Including Adhesive)	2 to 3 mils (50 to 75 microns), $\pm 10\%$
Gloss Level in Gloss Units (GU)	At 60°: CrystalVue Silver & Glass EtchVue: 8 ± 4 ; EtchVue: 30 ± 5
Release Liner	78# Bleached Kraft
Standard Width/Length	24 & 48 in. x 25 & 100 ft. (61 & 122 cm x 7.62 & 30.48 m). Custom sizes available.
Core Size	3 in.
Printing (Optional)	Solvent, eco-solvent, UV, thermal transfer or screen printing
Installation	Dry or wet; wet application recommended for larger graphics. Premasking is recommended for plotter-cut graphics with letters or designs that have cutouts within the design. Suitable for flat or moderately curved surfaces. Apply to clean surface. Use mild soap and water; rinse well. Do NOT use ammonia, Windex® or other solvent-based glass cleaner prior to application. For wet application, lightly spray the mounting surface with water or a suitable application fluid, remove liner, position the film as desired, and use a squeegee to remove water/fluid. Use a soft-edged squeegee designed specifically for wet application to prevent scratches and wrinkles. For detailed instructions, please refer to the CrystalVue™, EtchVue™ and Glass EtchVue™ Installation Instructions.
Minimum Application Temp.	40° F (4° C)
Repositionable	Yes, while film is still wet during wet application.
Outdoor Durability	5 years
Shrinkage & Gasoline Resistance	Excellent
Removal	Remove by peeling from surface. Remove any adhesive residue on older installations, if necessary.

Other CrystalVue™ Products



CrystalVue is also available in Gold (CFCYVGD), Green (CFCYVGN), Blue (CFCYVB) and Rose (CFCYVR) by special order. Contact us for more information.

Subject to change without notice

The above information is based on tests believed to be reliable and is presented for reference and illustration of general product characteristics only; it does not constitute a warranty. Purchasers should independently determine, prior to use, the suitability of the product for their specific application and print methods, if applicable. CLEAR FOCUS cannot be held liable for any misuse, damage or losses as specified in its warranty.

CLEAR FOCUS Imaging, Inc. 60 Maxwell Court, Santa Rosa, CA 95401 USA
Tel. (707) 544-7990 • Fax: (707) 544-1886 • E-mail: headoffice@clearfocus.com • Web: www.clearfocus.com
USA toll-free (800) 307-7990