



## ImageVue®

**Perforation pattern:**

Approx. 65/35 (35% open)

**Perforation size:**

0.06 in. (1.5 mm)

**Film:**

8-mil calendered PVC on a 3-in. core

**Standard roll sizes:**

54 in. x 25 ft.

54 & 60 in. x 100 & 1000 ft.

**Application:**

Decals, POP/retail posters, other small-format & graphics-intensive window signage

**Product code:**

CFEABWIV



**CLEAR FOCUS Imaging, Inc.**



**Exterior Mount Product Specifications**

**Product Code: CFEABWIV**

8-mil white/black composite PVC with clear removable acrylic pressure-sensitive adhesive and a release liner consisting of clear PET film laminated to perforated paper to absorb ink.

Applications	Windows, glass doors or other transparent surfaces.
Composition	White/black PVC with clear pressure-sensitive adhesive coating and a release liner consisting of clear PET film laminated to perforated paper to absorb ink.
Open Area	35% (approx.)
Vinyl Thickness (incl. adhesive)	8 mils (.008 in./203 microns), approx.
Release Liner Thickness	7 mils (.007 in./178 microns), approx.
Adhesive Thickness	1 mil (.001 in./25 microns), approx.
Perforation Diameter	.060 in. (1.5 mm)
Standard Widths/Lengths	54 & 60 in. x 100 & 1000 ft. (1.37 & 1.52 x 30.48 & 304.8 m); 54 in. x 25 ft (1.37 x 7.62 m) Custom sizes available by special order.
Dimensional Stability	Good
Minimum Application Temperature	40° F (4° C)
Service Temperature Range	0° F to 140° F (-17° C to 60° C)
Expected Lifetime Exterior	2 to 3 years. 6 months for clean removal. Adhesion may increase with time.
Water Resistance	Fair. Immersion in water not recommended. If exposed to rain, an optically clear, compatible overlamine can be used to prevent holes from filling with water.
Humidity Resistance	Fair
Solvent Resistance	Good
Storage Stability	1-year shelf life when stored at 70° F (21° C) and 50% relative humidity.
Colors Available	White on print side and black on adhesive side.
Printing	Use standard vinyl inks. Print on the vinyl side, not on the release liner. Compatible with screen printing; inkjet printing using solvent, eco-solvent, mild solvent, latex (with solid paper liner) and UV-cure inks; thermal transfer; electrostatic transfer; and airbrushing.
Application	Apply to clean, dry glass surface. Use plain soap and water, rinse and dry glass well. Do NOT use ammonia, Windex® or other solvent-based glass cleaners prior to application. <b>Not for use on vehicle windows because of reduced visibility.</b>
Removal	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

**Other ImageVue Products**

<b>ImageVue with a White PET Liner</b> Code: CFEABWIVWL
<b>ImageVue with a Solid Paper Liner</b> Code: CFEABWIVSL

Features a patented white PET liner consisting of white PET film laminated to perforated paper to absorb ink and to facilitate sensing of media by printer. Compatible with all printing methods listed above, except latex inks. Custom order.

Features an unperforated solid paper liner. Recommended for latex inks. Not compatible with UV-cure printers. Custom order.

Subject to change without notice

It is the responsibility of purchasers to independently verify, prior to use, the suitability of the products for their specific applications and print methods. CLEAR FOCUS cannot be held liable for any misuse, damage or losses as specified in its product warranty.