PVSee™

Film: 3.5-mil gloss clear calendered PVC on a 3-in. core

Standard roll size: 54 in. x 100 & 1000 ft.

Application: Point-of-purchase, retail, trade show, decorative, architectural and other window graphics applications

Product code: CFPVSSL

CLEAR FOCUS Imaging, Inc.

CLEAR FOCUS PVSee™ FILM — Flexible Vinyl

Interior/Exterior Adhesive Mount Product Data — Product Code: CFPVSSL

3.5-mil gloss clear vinyl with clear solvent removable pressure-sensitive adhesive and a 90# smooth paper liner for excellent wet-out clarity.

Note: PVSee is an unperforated window graphics film.

Applications	Windows, glass doors, light boxes and other transparent or backlit surfaces. Ideally suited for point of purchase, retail, trade show and decorative applications.
Composition	Gloss clear calendered PVC with clear pressure-sensitive adhesive
Vinyl Thickness (including adhesive)	4 mils (101 microns/0.004 in)
Release Liner	90# ultra-smooth paper for optimum wet-out clarity
Standard Widths/Lengths	54 in. x 100 & 1000 ft. (1.37 x 30.48 & 304.8 m) Custom sizes available.
Color and Finish	Clear Gloss
Printing	Standard vinyl inks recommended. Print on clear film, not on liner. Compatible with screen printing; inkjet printing using solvent, eco-solvent and mild solvent inks (for denser colors use 2 passes); UV-cure; thermal transfer; and airbrushing. Reverse-print image for interior-mount applications. **Note: Any text will display in reverse on one side.**
Installation	Apply to clean surface. Use plain soap and water, rinse well. Do NOT use ammonia, Windex® or other solvent-based glass cleaners prior to application. Wet application is recommended. Lightly spray the mounting surface with water or a suitable application fluid, remove liner, position the poster as desired, and use a squeegee to remove water/fluid. Use a soft-edged squeegee designed specifically for wet application to protect the graphic from scratches. For detailed instructions, please refer to the PVSee installation instruction sheet.

Typical Characteristics	15 min.	24 hr.
Target Adhesion Values (PSTC-1, 180° peel @ 12"/min., 73° F, on stainless steel)	30 oz.	40 oz.
Minimum Application Temperature	50° F (10° C)	
Service Temperature Range	-40° F to +180° F (-40° C to +82° C)	
Shelf Life @ 73° F, 50% RH	2 years	
Outdoor Durability	3 years	

Chemical Resistance	
Distilled Water (24 hr.)	No Effect
Detergent (24 hr.)	No Effect
10% HCl (10 min.)	No Effect
10% Ammonium Hydroxide (10 min.)	No Effect
Anti-Freeze (24 hr.)	No Effect
SAE 20 Motor Oil (24 hr.)	No Effect
Gasoline (1 hr.)	No Effect

Removal	Remove by peeling from surface. Remove any adhesive residue on older installations, if necessary.

Subject to change without notice

It is the responsibility of purchasers to independently verify, prior to use, the suitability of the products for their specific applications and print methods. CLEAR FOCUS cannot be held liable for any misuse, damage or losses as specified in its product warranty.

CLEAR FOCUS Imaging, Inc. 60 Maxwell Court, Santa Rosa, CA 95401 USA
Tel. (707) 544-7990 • Fax: (707) 544-1886 • E-mail: headoffice@clearfocus.com • Web: www.clearfocus.com
USA toll-free (800) 307-7990