

CLEAR FOCUS ClassicVue™ FILM

Exterior Mount Product Specifications

Flexible Vinyl

Product Code: CFEABW

Black/White flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS:	Windows, glass doors and other transparent surfaces
Makeup:	Black/White PVC laminate with clear pressure-sensitive adhesive coating and release liner.
Open Area:	Approximately 50%
Vinyl Thickness:	.008" (.2 mm)
Release Liner Thickness:	.007" (.17 mm)
Adhesive Thickness:	.001" (.02 mm)
Perforation Size:	.060" (1.5 mm)
Dimensional Stability:	Good
Minimum Application Temperature:	40° F (4° C)
Service Temperature Range:	0° F to 140° F (-17° C to 60° C)
Expected Lifetime Exterior:	Two to three years. Six months for clean removal. Adhesion may increase with time.
Water Resistance:	Very good. If exposed to rain, printed image can be laminated to prevent holes from filling with water.
Humidity Resistance:	Fair
Solvent Resistance:	Good
Storage Stability:	One-year shelf life when stored at 70° F (21° C) and 50% relative humidity.
Colors Available:	White print side and black adhesive side.
Printing:	Standard vinyl inks recommended. Print on the white side, not on the release liner. Compatible with screen printing; inkjet printing using solvent, eco-solvent, mild solvent and UV-curable inks; thermal transfer; electrostatic transfer; and airbrushing.
Installation:	Apply to clean, dry glass surface. Use plain soap and water, rinse and dry glass well. Do not use ammonia or other solvent-based glass cleaners prior to application.
Removal:	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

CLEAR FOCUS Imaging, Inc., 60 Maxwell Court, Santa Rosa, CA 95401, USA

Telephone (707) 544-7990 Fax (707) 544-1886

E-mail: headoffice@clearfocus.com Website www.clearfocus.com