



Exterior Mount Product Specifications

Product Code: CFEABW

8-mil white/black composite PVC with clear removable acrylic pressure-sensitive adhesive and a solid release liner.

Applications	Windows, glass doors and other transparent surfaces
Composition	White/black PVC laminate with clear pressure-sensitive adhesive coating and a solid release liner.
Open Area	50% (approx.)
Vinyl Thickness (incl. adhesive)	8 mils (.008 in./203 microns), approx.
Release Liner Thickness	7 mils (.007 in./178 microns), approx.
Adhesive Thickness	1 mil (.001 in./25 microns), approx.
Perforation Diameter	.060 in. (1.5 mm)
Standard Widths/Lengths	18, 36 & 54 in. x 100 & 1000 ft. (45.72, 91.44 & 137 cm x 30.48 m & 304.8 m) and 54 in. x 25 ft. (137 cm x 7.62 m) Custom sizes available by special order.
Dimensional Stability	Good
Minimum Application Temperature	40° F (4° C)
Service Temperature Range	0° F to 140° F (-17° C to 60° C)
Expected Lifetime Exterior	2 to 3 years. 6 months for clean removal. Adhesion may increase with time.
Water Resistance	Fair. Immersion in water not recommended. If exposed to rain, the use of an optically clear, compatible overlaminates is recommended to prevent holes from filling with water.
Humidity Resistance	Fair
Solvent Resistance	Good
Storage Stability	1-year shelf life when stored at 70° F (21° C) and 50% relative humidity
Colors Available	White on print side and black on adhesive side.
Printing	Use standard vinyl inks. Print image on white (non-adhesive) side. Compatible with screen printing; inkjet printing using solvent, eco-solvent, mild solvent and UV-curable inks; thermal transfer; electrostatic transfer; and airbrushing.
Application	Apply to clean, dry glass surface. Use mild soap and water, rinse and dry glass well. Do NOT use ammonia, Windex® or other solvent-based glass cleaner prior to application.
Removal	Remove by peeling from surface. Remove any adhesive residue on older installations, if necessary.

Other ClassicVue Products

For the Gerber EDGE Printer Code: CFEABW15GX50
Standard ClassicVue with a Solid Liner Code: CFEABWSL

Features a special pin-feed edge specifically for use with the Gerber EDGE thermal transfer printer.

Features an unperforated solid paper liner for wet transfer and other applications requiring such a liner.