

CLEAR FOCUS ClassicVue™ FILM

Flexible Vinyl

Exterior Mount Product Specifications For the Arizona™ 180 Printer

Removable Adhesive

Black/White flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

| | |
|----------------------------------|---|
| APPLICATIONS: | Windows, glass doors or other transparent surfaces |
| Makeup: | Black/White PVC with clear pressure-sensitive adhesive coating and release liner. |
| Open Area: | Approximately 50% |
| Vinyl Thickness: | .008" (.2 mm) |
| Release Liner Thickness: | .007" (.17 mm) |
| Adhesive Thickness: | .001" (.02 mm) |
| Perforation Size: | .060" (1.5 mm) |
| Dimensional Stability: | Good |
| Minimum Application Temperature: | 40° F (4°C) |
| Service Temperature Range: | 0°F to 140° F (-17°C to 60°C) |
| Expected Lifetime Exterior: | Two to three years. Six months for clean removal. Adhesion may increase with time. |
| Water Resistance: | Very good. If exposed to rain, printed image should be laminated to prevent holes from filling with water. |
| Humidity Resistance: | Fair |
| Solvent Resistance: | Good |
| Storage Stability: | One-year shelf life when stored at 70°F (21° C) and 50% relative humidity. |
| Colors Available: | White print side and black adhesive side. |
| Printing: | Standard vinyl inks recommended. Print on the white side of the film, not on the release liner. |
| Installation: | Apply to clean, dry glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners as they may have an adverse effect on the adhesive. |
| Removal: | Remove by peeling from surface. Remove adhesive residue on older installations, if necessary. |
| Arizona Specifications: | Film is reverse laminated and rolled print side in on a 3" core. |

Arizona is a trademark of Raster Graphics, Inc.

CLEAR Focus Imaging, Inc., 60 Maxwell Court, Santa Rosa, CA 95401 USA
Telephone (707) 544-7990 Fax (707) 544-1886
E-mail: headoffice@clearfocus.com Website www.clearfocus.com