

# CLEAR FOCUS ClassicVue™ FILM

**15" Flexible Vinyl  
for GERBER EDGE™**

## Exterior Adhesive Mount Product Specifications

Removable Adhesive

Edge perforated for use on the Gerber Edge™ (trademark of Gerber Scientific Products Inc.)

Flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors or other transparent surfaces
MAKEUP	Black/White PVC laminate with clear pressure-sensitive adhesive coating with release liner
OPEN AREA	50% (approximately)
VINYL THICKNESS	.008" (.2 mm)
RELEASE LINER THICKNESS	.007" (.17 mm)
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.060" (1.5 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40°F (4EC)
SERVICE TEMPERATURE RANGE	0EF to 140EF (-17EC to 60EC)
EXPECTED LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
WATER RESISTANCE	Not recommended where immersed in water.
HUMIDITY RESISTANCE	Fair
SOLVENT RESISTANCE	Good
STORAGE STABILITY	One-year shelf life when stored at 70°F (21EC) and 50% relative humidity.
COLORS AVAILABLE	White/black laminate (white on one side, black on the other side)
APPLICATION	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

**CLEAR FOCUS Imaging, Inc.**, 60 Maxwell Court, Santa Rosa, California 95401, USA

Tel: (707) 544-7990 Fax: (707) 544-1886

E-Mail: [headoffice@clearfocus.com](mailto:headoffice@clearfocus.com) Website: [www.clearfocus.com](http://www.clearfocus.com)