

CLEAR FOCUS ImageJetVue™ FILM

Exterior Adhesive Mount InkJet Product Specifications

Flexible Vinyl

Removable Adhesive

Black/White flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors or other transparent surfaces
MAKEUP	Black/White PVC laminate, inkjet-receptive coated, with clear pressure-sensitive adhesive coating with release liner
OPEN AREA	35% (approximately)
VINYL THICKNESS	.008" (.2 mm)
RELEASE LINER THICKNESS	.007" (.17 mm)
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.060" (1.5 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40°F (4EC)
SERVICE TEMPERATURE RANGE	0EF to 140EF (-17EC to 60EC)
EXPECTED ADHESIVE VINYL LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
EXPECTED IMAGE LIFETIME	Varies according to ink type, use of clear coat or overlaminate, and conditions under which image is displayed. Conduct test prior to production.
WATER RESISTANCE	Not recommended where immersed in water.
HUMIDITY RESISTANCE	Fair
STORAGE STABILITY	One-year shelf life when stored at 70°F (21EC) and 50% relative humidity
COLORS AVAILABLE	White/black laminate (white on one side, black on the other)
PRINTING	Pigmented or dye-based inkjet inks recommended. Print image on non-adhesive side (white side) of the product, not on release liner.
APPLICATION	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application. Not for use on vehicle windows because of reduced visibility.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

CLEAR FOCUS Imaging, Inc., 60 Maxwell Court, Santa Rosa, California 95401, USA
Tel. (707) 544-7990 Fax (707) 544-1886
E-Mail: headoffice@clearfocus.com Website: www.clearfocus.com