

# CLEAR FOCUS JetVue™ FILM with Solid Liner

Flexible Vinyl

Removable Adhesive

## Exterior Adhesive Mount Inkjet Product Specifications

### **Black/White flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.**

APPLICATIONS	Windows, glass doors or other transparent surfaces
MAKEUP	Black/White PVC laminate, inkjet-receptive coated, with clear pressure-sensitive adhesive coating with release liner
OPEN AREA	50% (approximately)
VINYL THICKNESS	.008" (.2 mm)
RELEASE LINER	.007" (.17 mm) thick. Unperforated; without polyester laminate. Solid liner extends approximately 1/4" (6.35 mm) beyond vinyl on each edge.
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.080" (2.0 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40°F (4EC)
SERVICE TEMPERATURE RANGE	0EF to 140EF (-17EC to 60EC)
EXPECTED ADHESIVE VINYL LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
EXPECTED IMAGE LIFETIME	Varies according to types of inks used, use of clear coat or overlamine, and conditions under which image is displayed. Use of a clear coat or overlamine will increase life of image. Conduct test prior to production.
WATER RESISTANCE	Not recommended where immersed in water. An overlamine or clear coat is recommended where image is exposed to excessive moisture.
HUMIDITY RESISTANCE	Fair
STORAGE STABILITY	One-year shelf life when stored at 70°F (21EC) and 50% relative humidity
COLORS AVAILABLE	White/black laminate (white on one side, black on the other)
PRINTING	Pigmented or dye-based aqueous inkjet inks recommended. Print image on non-adhesive side (white side) of the product, not on release liner. (Note: Use JetVue with standard liner, not solid liner, when printing with oil-based inks.)
APPLICATION	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

**CLEAR FOCUS** Imaging, Inc., 60 Maxwell Court, Santa Rosa, California 95401, USA

Tel. (707) 544-7990 Fax (707) 544-1886

E-Mail: [headoffice@clearfocus.com](mailto:headoffice@clearfocus.com) Website: [www.clearfocus.com](http://www.clearfocus.com)