

CLEAR FOCUS SuperVue™ FILM

with Solid Liner

Interior Mount Product Specifications

Flexible Vinyl

Removable Adhesive

Clear flexible 6-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors or other transparent surfaces
MAKEUP	Clear PVC with clear pressure-sensitive adhesive coating with release liner
OPEN AREA	50% (approximately)
VINYL THICKNESS	.006" (.15 mm)
RELEASE LINER THICKNESS	.007" (.17 mm). Unperforated liner; without polyester laminate. Solid liner extends approximately ¼" (6.35 mm) beyond vinyl on each edge.
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.080" (2 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40°F (4EC)
SERVICE TEMPERATURE RANGE	0EF to 140EF (-17EC to 60EC)
EXPECTED LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
WATER RESISTANCE	Not recommended where immersed in water.
HUMIDITY RESISTANCE	Fair
SOLVENT RESISTANCE	Good
STORAGE STABILITY	One-year shelf life when stored at 70°F (21EC) and 50% relative humidity.
COLORS AVAILABLE	Clear
PRINTING	Standard vinyl inks recommended. 1) Print reverse image (mirror image) on clear vinyl. 2) Next, print a complete coat of opaque white. 3) Lastly, print a complete coat of opaque black.
APPLICATION	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

CLEAR FOCUS Imaging, Inc., 60 Maxwell Court, Santa Rosa, California 95401 USA
Tel. (707) 544-7990 Fax (707) 544-1886
E-mail: headoffice@clearfocus.com Website: www.clearfocus.com