

CLEAR FOCUS SuperVue[®] FILM

with Solid Paper Liner
Interior Mount Product Specifications

Flexible Vinyl
Removable Adhesive

Clear flexible 6-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors or other transparent surfaces
COMPOSITION	Clear PVC with clear pressure-sensitive adhesive coating with an unperforated solid paper release liner.
OPEN AREA	50% (approximately)
VINYL THICKNESS	.006" (152.4 microns)
RELEASE LINER THICKNESS	.007" (178 microns). Solid paper release liner extends approximately ¼" (6.35 mm) beyond vinyl on each edge.
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.080" (2 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40°F (4°C)
SERVICE TEMPERATURE RANGE	0°F to 140°F (-17°C to 60°C)
EXPECTED LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
WATER RESISTANCE	Not recommended where immersed in water.
HUMIDITY RESISTANCE	Fair
SOLVENT RESISTANCE	Good
STORAGE STABILITY	One-year shelf life when stored at 70°F (21°C) and 50% relative humidity.
COLOR AVAILABLE	Clear
PRINTING	Standard vinyl inks recommended. Print on the vinyl side, not on the release liner. Most suitable printing method is screen printing in the following sequence: 1) Print reverse image (mirror image) on clear vinyl. 2) Apply a full coat of opaque white ink. 3) Print a full coat of opaque black ink.
APPLICATION	To clean glass surface prior to applying graphics, use mild soap and water, rinse and dry the glass well. Do <u>not</u> use ammonia or other solvent-based glass cleaners (e.g., Windex [®]) prior to application.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

CLEAR FOCUS Imaging, Inc., 60 Maxwell Court, Santa Rosa, California 95401 USA
Tel. (707) 544-7990 Fax (707) 544-1886
E-mail: headoffice@clearfocus.com Website: www.clearfocus.com