

# CLEAR FOCUS SuperVue™ FILM

## Exterior Adhesive Mount Product Specifications

Flexible Vinyl

Product Code: CFEABWSV

Black/White flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors and other transparent surfaces
MAKEUP	Black/White PVC laminate with clear pressure-sensitive adhesive coating and release liner.
OPEN AREA	50% (approximately)
VINYL THICKNESS	.008" (.2 mm)
RELEASE LINER THICKNESS	.007" (.17 mm)
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.080" (2 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40° F (4EC)
SERVICE TEMPERATURE RANGE	0EF to 140EF (-17EC to 60EC)
EXPECTED LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
WATER RESISTANCE	Not recommended where immersed in water.
HUMIDITY RESISTANCE	Fair
SOLVENT RESISTANCE	Good
STORAGE STABILITY	One-year shelf life when stored at 70°F (21EC) and 50% relative humidity
COLORS AVAILABLE	White/black laminate (white on the print side, black on the adhesive side)
PRINTING	Standard vinyl inks recommended. Print image on white side of the product, not on release liner. Compatible with screen printing; inkjet printing using solvent, eco-solvent, mild solvent and UV-curable inks; thermal transfer; electrostatic transfer; and airbrushing.
APPLICATION	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.

**CLEAR FOCUS** Imaging, Inc. 60 Maxwell Court, Santa Rosa, California 95401, USA

Tel. (707) 544-7990 Fax (707) 544-1886

E-Mail: [headoffice@clearfocus.com](mailto:headoffice@clearfocus.com) Website: [www.clearfocus.com](http://www.clearfocus.com)