

# CLEAR FOCUS SuperVue™

## with Solid Liner for Wet Transfer Applications

### Exterior Adhesive Mount Product Specifications

Flexible Vinyl  
Product Code: CFEABWSVSL

Black/White flexible 8-mil vinyl film with removable clear acrylic pressure-sensitive adhesive.

APPLICATIONS	Windows, glass doors and other transparent surfaces
MAKEUP	Black/White PVC laminate with clear pressure-sensitive adhesive coating and release liner
OPEN AREA	50% (approximately)
VINYL THICKNESS	.008" (.2 mm)
RELEASE LINER	.007" (.17 mm) thick. Unperforated; without polyester laminate. Solid liner extends approximately 1/4" (6.35 mm) beyond vinyl on each edge.
ADHESIVE THICKNESS	.001" (.02 mm)
PERFORATION SIZE	.080" (2 mm) hole diameter
DIMENSIONAL STABILITY	Good
MINIMUM APPLICATION TEMPERATURE	40° F (4EC)
SERVICE TEMPERATURE RANGE	0EF to 140EF (-17EC to 60EC)
EXPECTED LIFETIME EXTERIOR	Two to three years. Six months for a clean removal. Adhesion may increase with time.
HUMIDITY RESISTANCE	Fair
SOLVENT RESISTANCE	Good
STORAGE STABILITY	One-year shelf life when stored at 70°F (21EC) and 50% relative humidity
COLORS AVAILABLE	White/black laminate (white on one side, black on the other)
PRINTING	Standard vinyl inks recommended. Print image on the white print side of the product, not on release liner. Compatible with screen printing; inkjet printing using solvent, eco-solvent and mild solvent inks; thermal transfer; electrostatic transfer; and airbrushing. For UV-curable inks, SuperVue with the regular liner is recommended.
APPLICATION	Apply to dry, clean glass surface. Use plain soap and water, rinse and dry the glass well. Do not use ammonia or other solvent-based glass cleaners prior to application.
REMOVAL	Remove by peeling from surface. Remove adhesive residue on older installations, if necessary.